
# **FLOAT ACCESSORIES**

Cable Clamp Assembly, Float Brackets, Pipe Mounting Bracket, Cable Weights, ETM w/ Piggy-Back Plug, Vertical Reed Switch, Anchor and Chain

## **CABLE WEIGHT**

Provides an accurate pivot point for suspended float switches.

Gripper teeth on clip and weight channel securely lock float cable into place





U.S. Patent 5.306.885

HOUSING: 1 pound, 12 ounce (0.8 kgs.), 2.8 inch diameter x 3.3 inch long (7.1 cm diameter x 8.4 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C).

CLIP: injection molded acetal plastic


WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2,


18/3, 16/2, 16/3, 14/2 and 14/3 SHIP WEIGHT: 2 lbs. (.907 kgs)

Part		
Number	Description	
1002230	Cable Weight	

#### **CABLE WEIGHT MINI**

Provides an accurate pivot point for suspended float switches.







HOUSING: 9.6 ounces (0.27 kgs.), 2.5 inch diameter x 2.5 inch long (6.35 cm diameter x 6.35 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C)

WIRE/CABLE ACCOMMODATED:

SJOW, SJTW, 18/2, 18/3

Part		
Number	Description	
1030356	Cable Weight Mini	

### **ELAPSED TIME METER WITH PIGGY-BACK PLUG**

Plugs into switched outlet or piggy-back switch of plugger control panel. Unit must be placed inside an enclosure.

Screws and mounting adhesive included.



Part Number	Description	
1022846	ETM w/120V piggy-back plug	
1032834	ETM w/230V piggy-back plug	

#### **VERTICAL REED SWITCH**

Control differential: .375 inch (1 cm)

Maximum angle from vertical: 5°

Electrical: 250 mAmps, 12-125 VAC, 50/60 Hz 500 mAmps, 6-12 VDC, 50/60 Hz

Housing and Float: 1.60 inch diameter x 6.7 inch long (4.06 cm X 17.01 cm), high impact, corrosion resistant PVC for use in sewage and non-potable water up to 120°F (50°C)



Part Number	Description	
1011027	10ft VRS 120V Bulk	
1016561	15ft VRS 120V Bulk	

### **ANCHOR**

10 lb. weight

Yellow, vinyl coated, mushroom style



Part		
Numbe	r Description	
101868	10 lb. Mushroom Anchor	

#### **CHAIN**

1/8" thickness

316 grade stainless steel

Available in one foot increments





PO Box 1708, Detroit Lakes, MN 56502 1-888-DIAL-SJE • 1-218-847-1317 1-218-847-4617 Fax